

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Canceled)

2. (Currently Amended) ~~The method of claim 1, further comprising:~~

A method of performing a multicast and broadcast transmission, comprising:  
receiving multicast/broadcast (M/B) packet data of a different network server,  
transmitted from a packet data serving node (PDSN), without setting links between the PDSN  
and target mobile stations for a M/B transmission within a mobile communication network;  
temporarily storing the received M/B packet data, performing an error control  
procedure, and transmitting the received M/B packet data to a plurality of mobile stations  
through a M/B packet data dedicated channel;  
processing the M/B packet data by only the target mobile stations that are  
identified by header information of the received M/B packet data;  
identifying the M/B packet data and general packet data and setting an internal  
process routine by a data packet controller;

Reply to Office Action of December 23, 2005

receiving the M/B packet data from the data packet controller and outputting a cellular data multicasting protocol service data unit (CDMP SDU) by adding a link header to the M/B packet data;

receiving the CDMP SDU, segmenting the CDMP SDU into a plurality of data units, and outputting a CDMP protocol data unit (PDU) generated by adding a multicast header to each separated data unit to a forward common traffic channel (f-ctch); and

segmenting the CDMP PDU inputted through the f-ctch into a prescribed size and transmitting a forward common data channel (F-CDCH) SDU generated by adding a Mux header and a CRC code to each segmented data unit to the plurality of mobile stations through a forward common data channel (F-CDCH ).

3. (Original) The method of claim 2, wherein the link header comprises identification information on the M/B packet data and unicast packet data.

4. (Original) The method of claim 2, wherein the link header comprises multicast group identifier information.

5. (Original) The method of claim 2, wherein the link header comprises a sequence number of the received M/B packet data.

6. (Original) The method of claim 2, wherein the inputted CDMP SDU is segmented to a maximum of 16 data units.
7. (Original) The method of claim 2, further comprising performing a forward error correction (FEC) coding.
8. (Original) The method of claim 2, wherein the multicast header comprises a sequence number of the received M/B packet data.
9. (Original) The method of claim 2, wherein the multicast header comprises multicast group identifier information.
10. (Previously Presented) The method of claim 2, wherein the CDMP SDUs are stored in a buffer for a predetermined time period.
11. (Original) The method of claim 2, wherein the F-CDCH SDU includes two local transmission units generated by adding the Mux header and the CRC code to each of the segmented data units.

12. (Currently Amended) ~~The method of claim 1, further comprising:~~

A method of performing a multicast and broadcast transmission, comprising:  
receiving multicast/broadcast (M/B) packet data of a different network server,  
transmitted from a packet data serving node (PDSN), without setting links between the PDSN  
and target mobile stations for a M/B transmission within a mobile communication network;  
temporarily storing the received M/B packet data, performing an error control  
procedure, and transmitting the received M/B packet data to a plurality of mobile stations  
through a M/B packet data dedicated channel;  
processing the M/B packet data by only the target mobile stations that are  
identified by header information of the received M/B packet data;  
removing a Mux header and a CRC code from a forward common data channel  
(F-CDCH) service data unit (SDU) received through a F-CDCH;  
extracting only CDMP protocol data units (PDUs) of a multicast group to which a  
corresponding mobile station has subscribed from a plurality of CDMP PDUs inputted through  
a forward common traffic channel (f-ctch);  
removing a multicast header of the extracted CDMP PDUs;  
generating a CDMP SDU block indicating that the extracted CDMP PDUs are  
aligned in good order;  
receiving the CDMP SDU block and completing an original CDMP SDU block  
without omission of any data unit;

generating the M/B packet data without a link header by removing a link header contained in the CDMP SDU block; and

transmitting the M/B packet data to an upper application layer.

13. (Original) The method of claim 12, further comprising performing a forward error correction (FEC) decoding by cellular data multicasting protocol (CDMP).

14. (Original) The method of claim 12, further comprising checking a sequence number contained in the multicast header to align the M/B packet data.

15. (Original) The method of claim 12, further comprising checking multicast group identifier information contained in the multicast header, in order to extract only the CDMP PDUs of the multicast group to which the corresponding mobile station has been subscribed.

16. (Original) The method of claim 12, further comprising transmitting a negative acknowledgment (NAK) signal to a base station side for a re-transmission of a corresponding packet when an error occurs in packet transmission.

17. (Original) The method of claim 16, wherein the NAK signal comprises a sequence number and a multicast group identifier of the corresponding packet.

18. (Currently Amended) The method of claim ~~1~~2, further comprising:  
transmitting the M/B packet data from a cellular data multicasting protocol (CDMP) to a common channel multiplex sub-layer using a forward common traffic channel (f-ctch) as a logical channel; and  
accessing multiple mobile stations of the plurality of mobile stations within a subscription area using a forward common data channel (F-CDCH) as a physical channel.
19. (Original) The method of claim 18, wherein at least one F-CDCH exists for each sector of a base station.
20. (Original) The method of claim 18, wherein if there are two F-CDCHs per sector of a base station, a first F-CDCH transmits a normal M/B packet and a second F-CDCH re-transmits a packet previously received with an error.
21. (Currently Amended) The method of claim ~~1~~2, wherein a base station side of the mobile communication network comprises a base station transceiver subsystem and a base station controller.

Reply to Office Action of December 23, 2005

22. (Currently Amended) The method of claim ~~1~~2, wherein each of the target mobile stations requests re-transmission of a packet from a base station side if there is an error in the received M/B packet data.

23. (Currently Amended) The method of claim ~~1~~2, further comprising:  
transmitting the M/B packet data from a common channel multiplex sub-layer to a cellular data multicasting protocol using a forward common traffic channel (f-ctch) as a logical channel; and

receiving the M/B packet data that has been transmitted to a plurality of unspecified mobile stations by a base station side using a forward common data channel (F-CDCH) as a physical channel.

24-28. (Canceled)

29. (Previously Presented) A method of performing data communication, comprising:  
receiving at least one of a multicast and a broadcast message with a subscriber terminal through a common channel;

determining whether the subscriber terminal is an intended recipient of the message based on header information of the message;

transmitting a negative acknowledgment message if the subscriber terminal is the intended recipient and the message is received with an error; and

disposing of the message if the subscriber terminal is not the intended recipient, without providing the content of the message to a man-machine interface of the subscriber terminal.

30. (Canceled)

31. (Original) The method of claim 29, wherein the subscriber terminal does not establish a link, which specifically identifies the subscriber terminal, with a packet data serving node.

32-38. (Canceled)

39. (Original) A base station of a mobile communication network, comprising:  
a data packet controller that identifies multicast/ broadcast (M/B) packet data and general packet data and sets an internal process routine;  
an M/B link access controller (LAC) that receives the M/B packet data from the data packet controller and outputs a cellular data multicasting protocol service data unit (CDMP SDU), which is generated by adding a link header to the M/B packet data;



a CDMP that receives the CDMP SDU, segments the CDMP SDU into a plurality of data units, and outputs a CDMP protocol data unit (PDU), generated by adding a multicast header to each separated data unit, to a forward common traffic channel (f-ctch); and

a common channel multiplex sub-layer that segments the CDMP PDU inputted through the f-ctch into a prescribed size and transmits a forward common data channel (F-CDCH) SDU, generated by adding a Mux header and a CRC code to each segmented data unit, to the plurality of mobile stations through a forward common data channel (F-CDCH ).

40. (Original) A mobile station, comprising:

a common channel multiplex sub-layer that removes a Mux header and a CRC code from a forward common data channel (F-CDCH) service data unit (SDU) received through a F-CDCH;

a cellular data multicasting protocol (CDMP) that extracts only CDMP protocol data units (PDUs) of a multicast group to which the mobile station has subscribed, among the CDMP PDUs inputted through a forward common traffic channel (f-ctch), removes a multicast header of the CDMP PDUs, and outputs a CDMP SDU block indicating that the CDMP PDUs are aligned;

an M/B link access controller (LAC) that receives the CDMP SDU block, completes an original CDMP SDU block without omitting a data unit, and outputs the M/B

Reply to Office Action of December 23, 2005

packet data without a link header, by removing the link header contained in the CDMP SDU block; and

a data packet controller that transmits the M/B packet data received from the M/B LAC to an upper application layer.

41. (Original) The method of claim 2, wherein the prescribed size is a Mux PDU type 3 size.

42. (Original) The method of claim 10, wherein the F-CDCH SDU includes two local transmission units generated by adding the Mux header and the CRC code to each of the segmented data units.

43. (Previously Presented) The method of claim 29, wherein the message is sent from a base station controller/packet control function of a mobile communication system and wherein the subscriber terminal is one of a plurality of mobile terminals.

Reply to Office Action of December 23, 2005

44. (Currently Amended) ~~The method claim 1, further comprising:~~

A method of performing a multicast and broadcast transmission, comprising:  
receiving multicast/broadcast (M/B) packet data of a different network server,  
transmitted from a packet data serving node (PDSN), without setting links between the PDSN  
and target mobile stations for a M/B transmission within a mobile communication network;  
temporarily storing the received M/B packet data, performing an error control  
procedure, and transmitting the received M/B packet data to a plurality of mobile stations  
through a M/B packet data dedicated channel;

processing the M/B packet data by only the target mobile stations that are  
identified by header information of the received M/B packet data;

providing a cellular data multicasting protocol service data unit (CDMP SDU) by  
adding a link header to the M/B packet data;

segmenting the CDMP SDU into a plurality of data units;

providing a CDMP protocol data unit (PDU) by adding a header to each data unit;

segmenting the CDMP PDU inputted into a prescribed size; and

transmitting a forward common data channel (F-CDCH) SDU generated by  
adding a Mux header and a CRC code to each segmented data unit to the plurality of mobile  
stations through a forward common data channel (F-CDCH ).

45. (Currently Amended) ~~The method of claim 1, further comprising:~~

A method of performing a multicast and broadcast transmission, comprising:  
receiving multicast/broadcast (M/B) packet data of a different network server,  
transmitted from a packet data serving node (PDSN), without setting links between the PDSN  
and target mobile stations for a M/B transmission within a mobile communication network;  
temporarily storing the received M/B packet data, performing an error control  
procedure, and transmitting the received M/B packet data to a plurality of mobile stations  
through a M/B packet data dedicated channel;  
processing the M/B packet data by only the target mobile stations that are  
identified by header information of the received M/B packet data;  
removing a Mux header and a CRC code from a forward common data channel  
(F-CDCH) service data unit (SDU) received through a F-CDCH;  
extracting only CDMP protocol data units (PDUs) of a multicast group to which a  
corresponding mobile station has subscribed from a plurality of CDMP PDUs;  
removing a multicast header of the extracted CDMP PDUs;  
generating a CDMP SDU block; and  
generating the M/B packet data without a link header by removing a link header  
contained in the CDMP SDU block.